TECHNICAL INFORMATION

Physical properties
Total Weight: 460g/m² (nominal)
Vinyl Weight: 370g/m² (nominal)
Substrate Type: Polyester/Cellulose Nonwoven
Substrate Weight: 90g/m² (nominal)

This product meets type II specification
Tensile Strength: MD 80 N/cm (nominal)
TD 60 N/cm (nominal)
Tear Strength: 8500 mN (nominal)

Roll size:
Made to order.
Produced in bespoke panels or running metres.

Pattern Repeat
Refers to design.

Fire Rating:
Class B when bonded
To a suitable substrate
(Class A2 – s1,d0 or better)
Class A ASTME-84 tunnel test

Adhesive:
Newmor Heavy.
Varies with substrate - please enquire.

Bacteria Resistance:
Contains an active Fungicide.

Light Fast:
Excellent Light Fastness
BS EN ISO 105-B02 7/8

Light reflective value (LRV)
Available on request.
In architecture, light reflectance value, is a measure of visible and usable light that is reflected from a surface when illuminated by a light source.

Specifications
Conforms to requirements of BS EN 15102, BS EN 259 and WA – Quality Standard W-101.

Stain/Chemical Resistance:
Pass ASTM D-1308-1987 Federal Spot Test.
Resistant to tempo rary stain ing of oils, fats, mild acids and alkalis.

Quality Assurance:
Our management systems and production procedures comply with ISO 9001 : 2015, the internationally recognised Quality Standard.

Availability:
Made to order, lead times available upon request.

Origin:
Designed, coloured, manufactured and stocked in the UK.

Warranty:
Newmor offers a five year warranty against manufacturing defects.
Full details available on application.

Samples:
Larger samples are readily available on request.

Maintenance:
Refer to full Digital Cleaning and Maintenance instructions, available upon request or download from the Newmor website.

20% This product contains at least 20% recycled material