

ADITI CRUSH 69-Silk collection



NB: The portrayed colours may differ from reality.



69-2420 BURGUNDY


69-2430 LATTE


69-2431 SIENNA


69-2432 RAIN


69-2433 TEAL


69-2434 AUBURN


69-2435 DENIM


69-2436 NIGHT

Specification

Name	Aditi Crush	
Width approx.	110 cm - 43"	
Weight approx.	gr / lm oz / lnyd	: 215 : 6.9
Thickness	approx. 0.47 mm	
Composition	silk linen	: 42% : 58%
Weaving technique	jacquard woven	
Dyeing	yarn dyed	
Backing	reinforced woodpulp recycled polyester	: 70% : 30%
Repeat approx.	height width	: - : -
Hanging	random, non-reverse	

Scan QR-code for more details, visuals and video content.

Performance	Please contact info@tapetex.com for more detailed test reports.
Surface finish	A stain repellent finish prevents waterbased splashes penetrating and staining the material. Periodic vacuuming is recommended to prevent dust from building up on the materials surface.
Lightfastness	Test result as per ISO 105-B02:2014, Heraeus original Hanau Xenotest.
LRV values	Testing as per BS 8493:2008+A1:2010, Datacolor DC500.
Fire rating	ASTM E84 Class 1 or A and EUROCLASS (B s1 d0).
Permeability rating	Test result 63.7 as per ASTM E96-12, Method B, Water Vapor Transmission.
Indoor air quality	ASTM D6196, D5197 and D5116, Environmental Chamber Test. The testing followed UL 2821 "Greenguard Certification Program Method for Measuring and Evaluating Chemical Emissions".
REACH SVHC	Compliant as per Centexbel testing.



Treated with a stain repellent finish



Lightfastness: as per ISO 105-B02:2014 Xenotest




Light reflection: as per BS 8493: 2008+A1:2010 Datacolor DC500




Fire resistant: EU: B, s1-d0 US: ASTM E84 Class 1 or A



Permeability rating: 63.7, as per ASTM E96-12 Method B



Indoor air quality: ASTM D6196, D5197 and D5116



Sustainability
Silk is a 100% renewable natural resource. The backing is FSC certified, FSC A000531.
In production, all energy sources are either green, wind or hydro based and all processes are waterbased. The products do not contain PVC, chlorine, plasticizers, heavy metals or harmful dyes.

Supply and packing
Delivery from stock by the full linear meter or full linear yard. The average piece length of this quality is approx. 50 linear meter or 55 linear yards. However, as is common within the textile industry, it is not possible to establish a standard roll length. The wallcovering is reeled on to a cardboard core, wrapped in polyethylene and protective end caps are fixed. Each roll is then packed in individual cardboard boxes or tubes, which are also made out of FSC certified woodpulp.

Harmonized System as per the World Customs Organization and Origin
Textile Wallcovering, paper backed: 5905.00. Made in the Netherlands.

CE EN 15102

REACH

FSC Forest Stewardship Council, Certification FSC A000531.


Carbon Neutral Shipping

PVC FREE

100% BIO BASED


Hanging details

Hanging	Random, non-reverse. Precision trimmed for butt-joining by professional paper hangers. Installation advice supplied with every roll. Use rubber roller instead of spatula. Direction of hanging is printed on back of wallcovering.
Adhesive	Use a premixed heavy duty, clear vinyl adhesive, suitable for textile wallcovering.
Variation	There can be a variation between sample material and finished product. Stock cuttings are available for approval.



Precision trimmed | Sold by the meter/yard | Direction of hanging | Use a rubber roller | Don't use a spatula | Apply adhesive on the wall

View





"Freedom"

Aditi is full of character, ambience, vigour and vibrant colours, just like the home country of silk, India. The selection of the neutral, uncrushed qualities challenging the crushed, bold colours. This open-weave silk offers a lot of texture and surface interest due to the variance of weft yarns used and therefore never fails to impress.
Each item is a unique piece due to the nature of the raw material. In case of the crushed items, the unpredictable crush lines create an optical illusion; what seems so irregular and bumpy is in reality completely flat.

Aditi Crush 69-2436